

Promax 1020

P/N: 543-22332-00



The temperature-controlled model with load capacities of 5 kg

The 1000 series reciprocating shaker can be easily integrated into the modular [incubator system](#). This makes it possible to successfully run temperature controlled applications. The Promax 1020 can also be used to purify proteins at 4°C. With a platform size of 290 x 258 mm, there is enough space for the vessels used.

With a stroke of 32 mm and a speed of 30 – 250 rpm, a proper separation of the samples is guaranteed. The integrated timer function enables unattended operation so that you can concentrate on other tasks without worries. After the set time has elapsed, the acoustic signal signals the end of the shaking process.

Supplemented with the appropriate holder for [separatory funnels](#), a maximum of four pieces between 50 and 100 ml can be securely attached to the Promax 1020.

Promax 1020 - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	8 kg
Protection class DIN EN 60529	IP 40
Timer	Yes
Rotation speed range	30 - 250 rpm
Power input	50 W
Dimensions (w/d/h)	320 x 375 x 125 mm
Max. Load	5 kg
Operating Mode	timer or continuous
Rotation speed setting	digital
Orbit / Stroke	32 mm
Platform size	290 x 258 mm
Accessories included	non-skid rubber mat
Angle	-
Motion	reciprocating